## NSN 5985-00-480-1712

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-480-1712

Application Design:
Transmission line
Body Material:
Metal
Body Style:
Round, terminal/terminals in opposite surface
Body Surface Treatment:
Any acceptable
Overall Length:
Between 2.210 inches and 2.250 inches
Overall Diameter:
0.570 inches
Operating Tempurature Range:
-55.0/+120.0 degrees celsius
Voltage Standing Wave Ratio:
1.35
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Bnc
Power Rating:
Power Rating: 2.0 watts average and 3.0 kilowatts peak
<del>-</del>
2.0 watts average and 3.0 kilowatts peak
2.0 watts average and 3.0 kilowatts peak  Rf Signal Attenuation In Decibels:
2.0 watts average and 3.0 kilowatts peak  Rf Signal Attenuation In Decibels:  40.0
<ul><li>2.0 watts average and 3.0 kilowatts peak</li><li>Rf Signal Attenuation In Decibels:</li><li>40.0</li><li>Voltage Standing Wave Ratio Frequency Range:</li></ul>
2.0 watts average and 3.0 kilowatts peak  Rf Signal Attenuation In Decibels:  40.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+5.0 gigahertz
2.0 watts average and 3.0 kilowatts peak  Rf Signal Attenuation In Decibels:  40.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+5.0 gigahertz  Attenuation Accuracy Reference Frequency:
2.0 watts average and 3.0 kilowatts peak  Rf Signal Attenuation In Decibels:  40.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+5.0 gigahertz  Attenuation Accuracy Reference Frequency: 5.0 gigahertz
2.0 watts average and 3.0 kilowatts peak  Rf Signal Attenuation In Decibels:  40.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+5.0 gigahertz  Attenuation Accuracy Reference Frequency: 5.0 gigahertz  Attenuation Accuracy In Decibels:
2.0 watts average and 3.0 kilowatts peak  Rf Signal Attenuation In Decibels:  40.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+5.0 gigahertz  Attenuation Accuracy Reference Frequency: 5.0 gigahertz  Attenuation Accuracy In Decibels: -1.50/+1.50
2.0 watts average and 3.0 kilowatts peak  Rf Signal Attenuation In Decibels:  40.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+5.0 gigahertz  Attenuation Accuracy Reference Frequency: 5.0 gigahertz  Attenuation Accuracy In Decibels: -1.50/+1.50  Frequency Sensitivity Attenuation In Decibels:
2.0 watts average and 3.0 kilowatts peak  Rf Signal Attenuation In Decibels:  40.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+5.0 gigahertz  Attenuation Accuracy Reference Frequency: 5.0 gigahertz  Attenuation Accuracy In Decibels: -1.50/+1.50  Frequency Sensitivity Attenuation In Decibels: 1.50
2.0 watts average and 3.0 kilowatts peak  Rf Signal Attenuation In Decibels:  40.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+5.0 gigahertz  Attenuation Accuracy Reference Frequency: 5.0 gigahertz  Attenuation Accuracy In Decibels: -1.50/+1.50  Frequency Sensitivity Attenuation In Decibels: 1.50  Connection Type Per Function:
2.0 watts average and 3.0 kilowatts peak  Rf Signal Attenuation In Decibels:  40.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+5.0 gigahertz  Attenuation Accuracy Reference Frequency: 5.0 gigahertz  Attenuation Accuracy In Decibels: -1.50/+1.50  Frequency Sensitivity Attenuation In Decibels: 1.50  Connection Type Per Function:  Male input and female output
2.0 watts average and 3.0 kilowatts peak Rf Signal Attenuation In Decibels: 40.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+5.0 gigahertz Attenuation Accuracy Reference Frequency: 5.0 gigahertz Attenuation Accuracy In Decibels: -1.50/+1.50 Frequency Sensitivity Attenuation In Decibels: 1.50 Connection Type Per Function: Male input and female output Mounting Method:
2.0 watts average and 3.0 kilowatts peak  Rf Signal Attenuation In Decibels:  40.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+5.0 gigahertz  Attenuation Accuracy Reference Frequency: 5.0 gigahertz  Attenuation Accuracy In Decibels: -1.50/+1.50  Frequency Sensitivity Attenuation In Decibels: 1.50  Connection Type Per Function:  Male input and female output  Mounting Method:  Connector
2.0 watts average and 3.0 kilowatts peak Rf Signal Attenuation In Decibels: 40.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+5.0 gigahertz Attenuation Accuracy Reference Frequency: 5.0 gigahertz Attenuation Accuracy In Decibels: -1.50/+1.50 Frequency Sensitivity Attenuation In Decibels: 1.50 Connection Type Per Function: Male input and female output Mounting Method: Connector Terminal Type And Quantity:

## NSN 5985-00-480-1712

Fixed Attenuator - Page 2 of 2



Fsc Application Data	Fsc Appl	ication	Data
----------------------	----------	---------	------

Antennas, waveguides, and related equipment

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

Yes - demil/mli

Fiig:

A20000