

View Online at <https://aerobasegroup.com/nsn/5985-00-481-8113>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Tubing Wall Construction Style:

Corrugated single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.705 inches all flanges and 0.707 inches all flanges

Flange Inside Height:

0.394 inches all flanges and 0.396 inches all flanges

Flange Outside Width:

1.298 inches all flanges and 1.328 inches all flanges

Flange Outside Height:

1.298 inches all flanges and 1.328 inches all flanges

Flange Depth:

0.298 inches all flanges and 0.328 inches all flanges

Flange Connecting Hole Diameter:

0.144 inches all flanges all connection facilities and 0.147 inches all flanges all connection facilities

Voltage Standing Wave Ratio:

1.25

Insertion Loss In Decibels:

0.40

Waveguide Outside Width:

Between 0.699 inches and 0.705 inches

Waveguide Inside Width:

Between 0.6195 inches and 0.6245 inches

Waveguide Inside Height:

Between 0.3085 inches and 0.3135 inches

Waveguide Outside Height:

Between 0.388 inches and 0.394 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole all flanges all connection facilities

Flange Style:

Cover type all flanges

Waveguide Length:

Between 26.900 inches and 27.100 inches

Flexibility:

Flexible single tubing segment

Material:

Rubber synthetic single tubing jacket

Precious Material And Location:

All surfaces silver

Precious Material:

Silver

Surface Treatment:

Silver all tubing segment and flange all surfaces

Style Designator:

Straight type

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A073a0