## NSN 5985-00-482-0454

Radio Frequency Transmission Line Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-482-0454 **Body Style:** Irregular **Overall Length:** 3.844 inches **Overall Height:** 2.001 inches **Overall Width:** 1.156 inches Frequency Rating: 0.0 megahertz and 500.0 megahertz single frequency rf power handling **Unthreaded Mounting Hole Diameter:** 0.136 inches Switch Type: Nontransfer **Distance Between Mounting Facility Centers:** 1.500 inches single mounting facility pattern **Longest Horizontal Distance Between Mounting Centers:** 0.625 inches single mounting facility pattern **Longest Vertical Distance Between Mounting Centers:** 1.500 inches single mounting facility pattern **Operating Tempurature Range:** +0.0/+54.0 degrees celsius **End Application:** Transmitting set, radio an/frt-83 **Insertion Loss In Decibels:** 0.05 single **Coaxial Connector Series Designation: Connector End Design:** Female Rf Power Handling Capability: 2.0 watts average single Minimum Crosstalk Rating In Decibels: 30.0 single **Actuator Operating Method:** Relay **Actuator Voltage In Volts:** 28.0 **Switch Operation Sequence:** 

Switch Operation Sec Makes before breaks Switching Time:

15.0 milliseconds

## NSN 5985-00-482-0454

Radio Frequency Transmission Line Switch - Page 2 of 2



Ouitab Datum Mashanian Tuna
Switch Return Mechanism Type:
Fail-safe
Pole Quantity:
1
Throw Quantity:
2
Coupling Position Quantity:
3
Mounting Facility Type And Quantity:
2 unthreaded hole
Mounting Facility Pattern:
Two position diagonal single mounting facility pattern
Special Features:
Contacts are coin silver
Material:
Aluminum body
Precious Material And Location:
Contact surfaces gold and connector surfaces silver
Precious Material:
Gold and silver
Surface Treatment:
Chromate body outside surfaces
Terminal Type And Quantity:
1 plug, coaxial
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A158a0