# NSN 5985-00-482-0930

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-482-0930

Cross	Sectional	Shape:

Internal, rectangular external, rectangular

#### **Tubing Wall Construction Style:**

Interlocked single tubing segment

Flange Quantity:

2

### Flange Inside Height:

0.311 inches all flanges

### Flange Outside Width:

1.312 inches all flanges

#### Flange Outside Height:

1.312 inches all flanges

#### Flange Inside Diameter:

1.000 inches all flanges

#### Flange Depth:

0.375 inches all flanges

### Flange Connecting Hole Diameter:

0.144 inches all flanges single connection facility

# **Voltage Standing Wave Ratio:**

1.15

# **Insertion Loss In Decibels:**

0.30

#### **Maximum Operating Pressure:**

34.0 pounds per square inch gage

# **Waveguide Longer Offset Distance:**

0.622 inches

# Flange Connecting Facility And Quantity:

4 unthreaded hole all flanges single connection facility

#### Flange Style:

Choke type all flanges

# Waveguide Length:

1.402 feet

### Flexibility:

Flexible single tubing segment

#### Material:

Rubber single tubing jacket

# **Precious Material And Location:**

Flange surface and all tubing surfaces silver

# **Precious Material:**

Silver

#### **Surface Treatment:**

Silver single tubing segment inside surfaces

# NSN 5985-00-482-0930

Waveguide Assembly - Page 2 of 2



	sig		

Straight type

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0