

View Online at <https://aerobasegroup.com/nsn/5985-00-482-7630>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

Bend Angle In Deg:

90.0 single bend h-plane

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.003 inches second flange

Flange Inside Height:

0.505 inches second flange

Flange Outside Width:

1.620 inches second flange

Flange Outside Height:

1.620 inches second flange

Flange Inside Diameter:

1.159 inches first flange

Flange Depth:

0.438 inches second flange

Flange Connecting Hole Diameter:

0.171 inches second flange all connection facilities

Voltage Standing Wave Ratio:

1.10

Waveguide Outside Width:

1.000 inches

Thread Size:

0.164 inches first flange all connection facilities

Waveguide Inside Width:

0.900 inches

Waveguide Inside Height:

0.400 inches

Waveguide Outside Height:

0.500 inches

Waveguide Longer Offset Distance:

2.550 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole second flange all connection facilities

Flange Style:

Cover type second flange

Special Features:

Test data document: c18876-10674760

Flexibility:

Rigid single tubing segment

Material:

Copper all tubing segment and flange

Surface Treatment:

Any acceptable all tubing segment and flange inside surfaces

Style Designator:

Corner type

Thread Series Designator:

Unc first flange all connection facilities

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A073a0