## NSN 5985-00-482-7630

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-482-7630

## **Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:** 

2b first flange all connection facilities

**Thread Direction:** 

Right-hand first flange all connection facilities

Bend Angle In Deg:

90.0 single bend h-plane

**Tubing Wall Construction Style:** 

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.003 inches second flange

Flange Inside Height:

0.505 inches second flange

Flange Outside Width:

1.620 inches second flange

Flange Outside Height:

1.620 inches second flange

Flange Inside Diameter:

1.159 inches first flange

Flange Depth:

0.438 inches second flange

Flange Connecting Hole Diameter:

0.171 inches second flange all connection facilities

**Voltage Standing Wave Ratio:** 

1.10

**Waveguide Outside Width:** 

1.000 inches

**Thread Size:** 

0.164 inches first flange all connection facilities

Waveguide Inside Width:

0.900 inches

**Waveguide Inside Height:** 

0.400 inches

**Waveguide Outside Height:** 

0.500 inches

**Waveguide Longer Offset Distance:** 

2.550 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole second flange all connection facilities

## NSN 5985-00-482-7630

Waveguide Assembly - Page 2 of 2



Flange Style: Cover type second flange **Special Features:** Test data document: c18876-10674760 Flexibility: Rigid single tubing segment Material: Copper all tubing segment and flange **Surface Treatment:** Any acceptable all tubing segment and flange inside surfaces Style Designator: Corner type **Thread Series Designator:** Unc first flange all connection facilities Shelf Life: N/a **Unit Of Measure: Demilitarization:** Yes - demil/mli

Fiig: A073a0