

View Online at <https://aerobasegroup.com/nsn/5985-00-483-0133>

**Thread Class:**

2b mounting facility hole

**Body Style:**

Rectangular

**Overall Length:**

0.556 inches

**Overall Height:**

0.800 inches

**Overall Width:**

1.090 inches

**Frequency Rating:**

20.0 megahertz and 400.0 megahertz single frequency operating

**Switch Type:**

Nontransfer

**Distance Between Mounting Facility Centers:**

0.500 inches single mounting facility pattern

**Operating Temperature Range:**

-55.0/+100.0 degrees celsius

**Voltage Standing Wave Ratio:**

1.25 single

**Insertion Loss In Decibels:**

0.60 single

**Rf Power Handling Capability:**

30.0 watts average single

**Minimum Crosstalk Rating In Decibels:**

45.0 single

**Actuator Operating Method:**

Relay

**Actuator Current Type And Rating In Amps:**

2.0 dc

**Actuator Voltage In Volts:**

27.5

**Switch Operation Sequence:**

Breaks before makes

**Switching Time:**

6.0 milliseconds

**Switch Return Mechanism Type:**

Fail-safe

**Pole Quantity:**

1

**Throw Quantity:**

2

**Rf Maximum Voltage Rating:**

350.0 volts rms

**Coupling Position Quantity:**

5

**Mounting Facility Type And Quantity:**

2 threaded hole

**Thread Size:**

0.112 inches mounting facility hole

**Mounting Facility Pattern:**

Two position in-line single mounting facility pattern

**Material:**

Metal body

**Test Data Document:**

13499-410-0471-010 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Series Designator:**

Unc mounting facility hole

**Terminal Type And Quantity:**

3 wire lead and 2 wire hook

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A158a0