NSN 5985-00-484-4895

Variable Attenuator - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/5985-00-484-4895

3
Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
1.500 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.500 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.500 inches
Overall Height:
0.750 inches
Overall Width:
1.500 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Voltage Standing Wave Ratio:
1.50
Coaxial Connector Series Designation:
N .
Power Rating:
6.0 watts average
Overall Attenuation Range In Decibels:
+0.0/+15.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 unthreaded hole
Frequency Range:
Between 2.900 gigahertz and 3.100 gigahertz
Overall Attenuation Accuracy In Decibels:
-0.075/+0.075
Adjustment Device Type And Quantity:
1 knob
Mounting Facility Pattern:
Four position rectangular
Test Data Document:
97942-128c361h03 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
2 connector, coaxial, female
Shelf Life:

NSN 5985-00-484-4895

Variable Attenuator - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A223a0