NSN 5985-00-485-0612



Fixed Attenuator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5985-00-485-0612 **Application Design:**

Transmission line		
Body Material:		
Any acceptable		
Body Style:		
Round, terminal/terminals in opposite surface		
Body Surface Treatment:		
Silver plated, qq-s-365		
Overall Length:		
5.984 inches		
Overall Diameter:		
1.000 inches		
Operating Tempurature Range:		
-40.0/+55.0 degrees celsius		
Voltage Standing Wave Ratio:		
1.55		
Input Impedance Rating In Ohms:		
50.0		
Output Impedance Rating In Ohms:		
50.0		
Coaxial Connector Series Designation:		
N		
Power Rating:		
7.0 watts average and 7.0 kilowatts peak		
Rf Signal Attenuation In Decibels:		
25.0		
Voltage Standing Wave Ratio Frequency Range:		
+150.0/+180.0 megahertz		
Attenuation Accuracy Reference Frequency:		
165.0 megahertz		
Attenuation Accuracy In Decibels:		
-0.20/+0.20		
Connection Type Per Function:		
Female input		
Mounting Method:		
Terminal		
Terminal Type And Quantity:		
2 connector		
Frequency Range:		
Between 150.000 megahertz and 180.000 megahertz		

Shelf Life: N/a

NSN 5985-00-485-0612

Fixed Attenuator - Page 2 of 2



Unit	Of	Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000