## NSN 5985-00-485-4876

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-485-4876

Application Design:
Transmission line
Body Style:
Cylindrical w/adjustment knob
Overall Length:
5.095 inches
Scale Linearity:
Linear
Overall Diameter:
1.830 inches
Operating Tempurature Range:
+0.0/+75.0 degrees celsius
Voltage Standing Wave Ratio:
1.20
Coaxial Connector Series Designation:
Sma
Power Rating:
200.0 milliwatts average
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.2
Overall Attenuation Range In Decibels:
+0.0/+60.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
15
Attenuation Per Step In Decibels:
1.0 and 10.0
Mounting Facility Type And Quantity:
2 connector
Frequency Range:
Between 40.000 megahertz and 80.000 megahertz
Overall Attenuation Accuracy In Decibels:
-1.000/+1.000
Adjustment Device Type And Quantity:
2 knob
Impedance Rating In Ohms:
50.0 input-output
Terminal Type And Quantity:
2 connector, coaxial, female
Shelf Life:
N/a

## NSN 5985-00-485-4876

Variable Attenuator - Page 2 of 2



**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0