## NSN 5985-00-487-3866

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-487-3866

Application Design:
Transmission line
Body Material:
Steel, stainless
Body Style:
Round, terminal/terminals in opposite surface
Body Surface Treatment:
Passivated, qq-p-35
Overall Length:
2.490 inches
Overall Diameter:
0.840 inches
Operating Tempurature Range:
+0.0/+55.0 degrees celsius
Voltage Standing Wave Ratio:
1.15 and 1.20 and 1.25
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
N
Power Rating:
2.0 watts average and 500.0 watts peak
Rf Signal Attenuation In Decibels:
6.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.0 gigahertz
Attenuation Accuracy In Decibels:
-0.30/+0.30
Frequency Sensitivity Attenuation In Decibels:
0.30
Connection Type Per Function:
Female input and male output
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 12.400 gigahertz
Shelf Life:
N/a

## NSN 5985-00-487-3866

Fixed Attenuator - Page 2 of 2



			ıre	

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000