NSN 5985-00-487-8463



Variable Attenuator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5985-00-487-8463 **Application Design:** Waveguide **Body Style:** Waveguide type **Overall Length:** 5.000 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 1.280 inches **Center To Center Distance Between Mounting Facilities Parallel To Width:** 1.220 inches **Overall Height:** 3.562 inches **Overall Width:** 1.625 inches **Unthreaded Mounting Hole Diameter:** 0.169 inches **Operating Tempurature Range:** -20.0/+65.0 degrees celsius **Voltage Standing Wave Ratio:** 1.20 **Power Rating:** 8.0 watts peak **Waveguide Flange Type:** Choke or cover **Waveguide Flange Designation:** Ug-135/u **Insertion Loss At Minimum Attenuation In Maximum Decibels:** 0.5 **Overall Attenuation Range In Decibels:** +0.0/+10.0 **Attenuation Variation Method:** Continuous **Mounting Facility Type And Quantity:** 4 terminal w/mounting holes Frequency Range: Between 10.250 gigahertz and 10.500 gigahertz **Adjustment Device Type And Quantity:** 1 knob

Mounting Facility Pattern:

Four position rectangular

Terminal Type And Quantity:

2 flange

NSN 5985-00-487-8463

Variable Attenuator - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A223a0