## NSN 5985-00-488-3492

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-488-3492

Application Design:
Transmission line
Body Style:
Cylindrical w/side terminals
Overall Length:
4.500 inches
Overall Width:
2.125 inches
Body Diameter:
1.500 inches
Shaft Diameter:
0.125 inches
Bushing Length:
0.937 inches
Shaft Length:
0.563 inches
Body Length:
3.000 inches
Operating Tempurature Range:
-20.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.10 and 1.20
Coaxial Connector Series Designation:
Bnc
Power Rating:
0.5 milliwatts average
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.2
Overall Attenuation Range In Decibels:
+0.0/+60.0
Attenuation Accuracy Reference Frequency:
30.0 megahertz
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 500.000 megahertz
Adjustment Device Type And Quantity:
1 shaft
Shaft Type:

Round

## NSN 5985-00-488-3492

Variable Attenuator - Page 2 of 2



Impedance Ra	ating In	Ohms:
--------------	----------	-------

50.0 input-output

**Terminal Type And Quantity:** 

2 connector, coaxial, female

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A223a0