

View Online at <https://aerobasegroup.com/nsn/5985-00-490-4429>

**Body Style:**

Rectangular

**Overall Length:**

4.800 inches

**Overall Height:**

Between 0.560 inches and 0.600 inches

**Overall Width:**

2.840 inches

**Frequency Rating:**

4.0 gigahertz and 8.0 megahertz single frequency operating

**Unthreaded Mounting Hole Diameter:**

0.140 inches

**Switch Type:**

Transfer

**Longest Horizontal Distance Between Mounting Centers:**

3.955 inches single mounting facility pattern and 3.965 inches single mounting facility pattern

**Longest Vertical Distance Between Mounting Centers:**

0.895 inches single mounting facility pattern and 0.905 inches single mounting facility pattern

**Operating Temperature Range:**

+0.0/+70.0 degrees celsius

**End Application:**

Test set, countermeasures an/alm-106

**Voltage Standing Wave Ratio:**

2.20 single

**Insertion Loss In Decibels:**

4.00 single

**Connector End Design:**

Female and female and male and female

**Rf Power Handling Capability:**

6.0 watts average single

**Minimum Crosstalk Rating In Decibels:**

30.0 single

**Actuator Operating Method:**

Solid state

**Switch Operation Sequence:**

Breaks before makes

**Switch Return Mechanism Type:**

Fail-safe

**Coupling Position Quantity:**

4

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Mounting Facility Pattern:**

Four position rectangular single mounting facility pattern

**Material:**

Stainless steel connecto (s)

**Unpackaged Unit Weight:**

8.000 ounces

**Terminal Type And Quantity:**

2 tab, solder lug and 1 plug, coaxial and 3 receptacle, coaxial

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A158a0