NSN 5985-00-491-0255

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-491-0255 **Application Design:** Transmission line **Body Material:** Aluminum **Body Style:** Rectangular, terminal/terminals on opposite surfaces **Body Surface Treatment:** Any acceptable **Overall Length:** 5.062 inches **Overall Height:** 2.000 inches **Overall Width:** 0.627 inches **Body Length:** 4.000 inches **Operating Tempurature Range:** +13.0 to 33.0 degrees celsius **Voltage Standing Wave Ratio:** Not rated **Input Impedance Rating In Ohms:** 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Ν **Power Rating:** 1.0 watts average and 500.0 watts peak Rf Signal Attenuation In Decibels: 6.0 **Attenuation Accuracy Reference Frequency:** 12.5 gigahertz **Attenuation Accuracy In Decibels:** -0.40 to 0.40 **Frequency Sensitivity Attenuation In Decibels: Temperature Sensitivity Attenuation In Decibels:** Not rated **Connection Type Per Function:**

Male input-output

Mounting Method:

Connector

NSN 5985-00-491-0255 Fixed Attenuator - Page 2 of 2



Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 12.500 gigahertz
Fsc Application Data:
Test kit, radar, fire control maintenance
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A20000