

View Online at <https://aerobasegroup.com/nsn/5985-00-491-1784>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

Tubing Wall Construction Style:

Interlocked single tubing segment

Tubing Twist Type:

Twistable single tubing segment

Tubing Twist Angle In Deg:

300.0 single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.611 inches first flange

Flange Inside Height:

0.394 inches second flange

Flange Outside Width:

1.312 inches second flange

Flange Outside Height:

1.312 inches second flange

Flange Inside Diameter:

0.909 inches first flange

Flange Depth:

0.375 inches first flange

Flange Connecting Hole Diameter:

0.144 inches second flange all connection facilities

Voltage Standing Wave Ratio:

1.15

Insertion Loss In Decibels:

0.20

Maximum Operating Pressure:

60.0 pounds per square inch gage

Waveguide Outside Width:

0.900 inches

Thread Size:

0.138 inches first flange all connection facilities

Waveguide Inside Width:

0.600 inches

Waveguide Inside Height:

0.311 inches

Waveguide Outside Height:

0.391 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole second flange all connection facilities

Flange Style:

Cover type second flange

Waveguide Length:

2.000 feet

Flexibility:

Flexible single tubing segment

Material:

Rubber single tubing jacket

Precious Material And Location:

Flange and tubing outside surface silver

Precious Material:

Silver

Surface Treatment:

Silver all tubing segment and flange outside surfaces

Style Designator:

Straight type

Thread Series Designator:

Unc first flange all connection facilities

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0