NSN 5985-00-492-7928



Variable Attenuator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5985-00-492-7928 **Application Design:** Waveguide **Body Material:** Aluminum **Body Style:** Waveguide type **Overall Length:** 8.750 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 4.750 inches **Center To Center Distance Between Mounting Facilities Parallel To Width:** 2.380 inches **Overall Height:** 6.530 inches **Overall Width:** 5.360 inches **Voltage Standing Wave Ratio:** 1.15 **Power Rating:** 10.0 watts average **Mounting Facility Screw Thread Series Designator:** Unc **Waveguide Flange Type:** Cover **Waveguide Flange Designation:** Ug-135/u **Insertion Loss At Minimum Attenuation In Maximum Decibels:** 1.0 **Overall Attenuation Range In Decibels:** +0.0/+60.0 **Attenuation Variation Method:** Continuous **Mounting Facility Type And Quantity:** 4 threaded hole Frequency Range: Between 8.200 gigahertz and 12.400 gigahertz

Mounting Thread Quantity:

20 per inch

Adjustment Device Type And Quantity:

1 knob

Mounting Facility Pattern:

Four position rectangular

NSN 5985-00-492-7928

Variable Attenuator - Page 2 of 2



Mounting Facility Screw Thread Diameter	Mounting	Facility	Screw	Thread	Diameter:
---	----------	-----------------	-------	---------------	-----------

0.250 inches

Terminal Type And Quantity:

2 flange

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

A223a0