NSN 5985-00-499-6323

Electrical Dummy Load - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5985-00-499-6323

Overall Length: 1.906 inches Impedance Rating In Ohms: 50.0 Overall Diameter: 0.594 inches Frequency Range Rating: +0.000/+12.400 gigahertz Voltage Standing Wave Ratio: 1.05 Coaxial Connector Series Designation: N Connector End Design: Male Power Rating: 10.000 watts average Voltage Standing Wave Ratio Frequency Range: +0.000/+4.000 gigahertz and +4.000/+10.000 gigahertz and +10.000/+12.400 gigahertz Termination Type: Connection coaxial Operating Position: Horizontal Cooling Method: Self-cooled Style Designator: Coaxial mounted Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Filig: A19800	
Impedance Rating In Ohms: 50.0 Overall Diameter: 0.594 inches Frequency Range Rating: +0.000/+12.400 gigahertz Voltage Standing Wave Ratio: 1.05 Coaxial Connector Series Designation: N Connector End Design: Male Power Rating: 10.000 watts average Voltage Standing Wave Ratio Frequency Range: +0.000/+4.000 gigahertz and +4.000/+10.000 gigahertz and +10.000/+12.400 gigahertz Termination Type: Connection coaxial Operating Position: Horizontal Cooling Method: Self-cooled Style Designator: Coaxial mounted Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Overall Length:
50.0 Overall Diameter: 0.594 inches Frequency Range Rating: +0.000/+12.400 gigahertz Voltage Standing Wave Ratio: 1.05 Coaxial Connector Series Designation: N Connector End Design: Male Power Rating: 10.000 watts average Voltage Standing Wave Ratio Frequency Range: +0.000/+4.000 gigahertz and +4.000/+10.000 gigahertz and +10.000/+12.400 gigahertz Termination Type: Connection coaxial Operating Position: Horizontal Cooling Method: Self-cooled Style Designator: Coaxial mounted Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	1.906 inches
Overall Diameter: 0.594 inches Frequency Range Rating: +0.000/+12.400 gigahertz Voltage Standing Wave Ratio: 1.05 Coaxial Connector Series Designation: N Connector End Design: Male Power Rating: 10.000 watts average Voltage Standing Wave Ratio Frequency Range: +0.000/+4.000 gigahertz and +4.000/+10.000 gigahertz and +10.000/+12.400 gigahertz Termination Type: Connection coaxial Operating Position: Horizontal Cooling Method: Self-cooled Style Designator: Coaxial mounted Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Impedance Rating In Ohms:
0.594 inches Frequency Range Rating: +0.000/+12.400 gigahertz Voltage Standing Wave Ratio: 1.05 Coaxial Connector Series Designation: N Connector End Design: Male Power Rating: 10.000 watts average Voltage Standing Wave Ratio Frequency Range: +0.000/+4.000 gigahertz and +4.000/+10.000 gigahertz and +10.000/+12.400 gigahertz Termination Type: Connection coaxial Operating Position: Horizontal Cooling Method: Self-cooled Style Designator: Coaxial mounted Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	50.0
Frequency Range Rating: +0.000/+12.400 gigahertz Voltage Standing Wave Ratio: 1.05 Coaxial Connector Series Designation: N Connector End Design: Male Power Rating: 10.000 watts average Voltage Standing Wave Ratio Frequency Range: +0.000/+4.000 gigahertz and +4.000/+10.000 gigahertz and +10.000/+12.400 gigahertz Termination Type: Connection coaxial Operating Position: Horizontal Cooling Method: Self-cooled Style Designator: Coaxial mounted Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Overall Diameter:
+0.000/+12.400 gigahertz Voltage Standing Wave Ratio: 1.05 Coaxial Connector Series Designation: N Connector End Design: Male Power Rating: 10.000 watts average Voltage Standing Wave Ratio Frequency Range: +0.000/+4.000 gigahertz and +4.000/+10.000 gigahertz and +10.000/+12.400 gigahertz Termination Type: Connection coaxial Operating Position: Horizontal Cooling Method: Self-cooled Style Designator: Coaxial mounted Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	0.594 inches
Voltage Standing Wave Ratio: 1.05 Coaxial Connector Series Designation: N Connector End Design: Male Power Rating: 10.000 watts average Voltage Standing Wave Ratio Frequency Range: +0.000/+4.000 gigahertz and +4.000/+10.000 gigahertz and +10.000/+12.400 gigahertz Termination Type: Connection coaxial Operating Position: Horizontal Cooling Method: Self-cooled Style Designator: Coaxial mounted Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Frequency Range Rating:
1.05 Coaxial Connector Series Designation: N Connector End Design: Male Power Rating: 10.000 watts average Voltage Standing Wave Ratio Frequency Range: +0.000/+4.000 gigahertz and +4.000/+10.000 gigahertz and +10.000/+12.400 gigahertz Termination Type: Connection coaxial Operating Position: Horizontal Cooling Method: Self-cooled Style Designator: Coaxial mounted Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	+0.000/+12.400 gigahertz
Coaxial Connector Series Designation: N Connector End Design: Male Power Rating: 10.000 watts average Voltage Standing Wave Ratio Frequency Range: +0.000/+4.000 gigahertz and +4.000/+10.000 gigahertz and +10.000/+12.400 gigahertz Termination Type: Connection coaxial Operating Position: Horizontal Cooling Method: Self-cooled Style Designator: Coaxial mounted Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Voltage Standing Wave Ratio:
Connector End Design: Male Power Rating: 10.000 watts average Voltage Standing Wave Ratio Frequency Range: +0.000/+4.000 gigahertz and +4.000/+10.000 gigahertz and +10.000/+12.400 gigahertz Termination Type: Connection coaxial Operating Position: Horizontal Cooling Method: Self-cooled Style Designator: Coaxial mounted Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	1.05
Connector End Design: Male Power Rating: 10.000 watts average Voltage Standing Wave Ratio Frequency Range: +0.000/+4.000 gigahertz and +4.000/+10.000 gigahertz and +10.000/+12.400 gigahertz Termination Type: Connection coaxial Operating Position: Horizontal Cooling Method: Self-cooled Style Designator: Coaxial mounted Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Coaxial Connector Series Designation:
Male Power Rating: 10.000 watts average Voltage Standing Wave Ratio Frequency Range: +0.000/+4.000 gigahertz and +4.000/+10.000 gigahertz and +10.000/+12.400 gigahertz Termination Type: Connection coaxial Operating Position: Horizontal Cooling Method: Self-cooled Style Designator: Coaxial mounted Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	N
Power Rating: 10.000 watts average Voltage Standing Wave Ratio Frequency Range: +0.000/+4.000 gigahertz and +4.000/+10.000 gigahertz and +10.000/+12.400 gigahertz Termination Type: Connection coaxial Operating Position: Horizontal Cooling Method: Self-cooled Style Designator: Coaxial mounted Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Connector End Design:
Voltage Standing Wave Ratio Frequency Range: +0.000/+4.000 gigahertz and +4.000/+10.000 gigahertz and +10.000/+12.400 gigahertz Termination Type: Connection coaxial Operating Position: Horizontal Cooling Method: Self-cooled Style Designator: Coaxial mounted Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Male
Voltage Standing Wave Ratio Frequency Range: +0.000/+4.000 gigahertz and +4.000/+10.000 gigahertz and +10.000/+12.400 gigahertz Termination Type: Connection coaxial Operating Position: Horizontal Cooling Method: Self-cooled Style Designator: Coaxial mounted Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Power Rating:
+0.000/+4.000 gigahertz and +4.000/+10.000 gigahertz and +10.000/+12.400 gigahertz Termination Type: Connection coaxial Operating Position: Horizontal Cooling Method: Self-cooled Style Designator: Coaxial mounted Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	10.000 watts average
Termination Type: Connection coaxial Operating Position: Horizontal Cooling Method: Self-cooled Style Designator: Coaxial mounted Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Voltage Standing Wave Ratio Frequency Range:
Connection coaxial Operating Position: Horizontal Cooling Method: Self-cooled Style Designator: Coaxial mounted Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	+0.000/+4.000 gigahertz and +4.000/+10.000 gigahertz and +10.000/+12.400 gigahertz
Operating Position: Horizontal Cooling Method: Self-cooled Style Designator: Coaxial mounted Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Termination Type:
Horizontal Cooling Method: Self-cooled Style Designator: Coaxial mounted Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Connection coaxial
Cooling Method: Self-cooled Style Designator: Coaxial mounted Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Operating Position:
Self-cooled Style Designator: Coaxial mounted Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Horizontal
Style Designator: Coaxial mounted Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Cooling Method:
Coaxial mounted Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Self-cooled
Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Style Designator:
N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Coaxial mounted
Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Shelf Life:
Demilitarization: Yes - demil/mli Fiig:	N/a
Yes - demil/mli Fiig:	Unit Of Measure:
Yes - demil/mli Fiig:	
Fiig:	Demilitarization:
-	Yes - demil/mli
A19800	Fiig:
	A19800