NSN 5985-00-500-7069

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-500-7069 **Application Design:** Transmission line **Overall Length:** 6.000 inches **Overall Height:** 2.125 inches **Overall Width:** 1.031 inches **Distance Between Mounting Facility Centers:** 5.625 inches **Power Rating:** 500.0 watts average **Mounting Facility Screw Thread Series Designator:** Unf **Overall Attenuation Range In Decibels:** +0.0/+10.0 **Attenuation Variation Method:** Stepped **Step Position Quantity: Attenuation Per Step In Decibels:** 1.0 and 2.0 and 3.0 and 4.0 **Mounting Facility Type And Quantity:** 2 threaded hole Frequency Range: Between 0.000 megahertz and 225.000 megahertz **Overall Attenuation Accuracy In Decibels:** -0.10/+0.10 **Mounting Thread Quantity:** 32 per inch **Mounting Facility Pattern:** Two position in-line **Mounting Facility Screw Thread Diameter:** 0.190 inches Impedance Rating In Ohms: 73.0 input-output

Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

NSN 5985-00-500-7069

Variable Attenuator - Page 2 of 2



Fiig:

A223a0