NSN 5985-00-506-5928

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-506-5928

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
2.600 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.750 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.880 inches
Overall Height:
2.310 inches
Overall Width:
2.060 inches
Operating Tempurature Range:
-55.0/+55.0 degrees celsius
Voltage Standing Wave Ratio:
0.02
Coaxial Connector Series Designation:
Bnc
Power Rating:
3.0 watts average
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.36
Overall Attenuation Range In Decibels:
+0.0/+15.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 threaded hole
Frequency Range:
Between 74.000 megahertz and 76.000 megahertz
Mounting Thread Quantity:
40 per inch
Adjustment Device Type And Quantity:
1 slotted screw
Mounting Facility Pattern:
Four position rectangular
Mounting Facility Screw Thread Diameter:

0.112 inches

NSN 5985-00-506-5928

Variable Attenuator - Page 2 of 2



	Impedance	Rating	ln	Ohms:
--	-----------	--------	----	-------

50.0 input-output

Terminal Type And Quantity:

2 connector, coaxial, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0