NSN 5985-00-509-0259



Variable Attenuator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5985-00-509-0259 **Application Design:** Waveguide **Body Style:** Waveguide type **Overall Length:** 3.750 inches Center To Center Distance Between Mounting Facilities Parallel To Width: 1.280 inches **Overall Width:** 1.625 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 1.220 inches **Voltage Standing Wave Ratio: Mounting Facility Screw Thread Series Designator:** Unc **Waveguide Flange Type:** Choke **Waveguide Flange Designation:** Ug-136/bu **Insertion Loss At Minimum Attenuation In Maximum Decibels:** 0.5 **Overall Attenuation Range In Decibels:** +0.0/+30.0 Frequency Range: Between 8.200 gigahertz and 12.400 gigahertz **Mounting Thread Quantity:** 32 per inch **Adjustment Device Type And Quantity:** 1 knob **Mounting Facility Pattern:** Four position rectangular **Mounting Facility Screw Thread Diameter:** 0.164 inches **Terminal Type And Quantity:** 2 flange Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

NSN 5985-00-509-0259

Variable Attenuator - Page 2 of 2



Fiig:

A223a0