# NSN 5985-00-509-1182

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-509-1182

# Application Design:

Transmission line

## Body Style:

Coaxial type

## Overall Length:

1.560 inches

# Center To Center Distance Between Mounting Facilities Parallel To Length:

0.340 inches

## Center To Center Distance Between Mounting Facilities Parallel To Width:

1.090 inches

## **Overall Height:**

1.100 inches

# Overall Width:

1.580 inches

## Unthreaded Mounting Hole Diameter:

0.140 inches

# Voltage Standing Wave Ratio:

1.20 and 1.50 and 2.00

# **Coaxial Connector Series Designation:**

Sma

#### **Power Rating:**

500.0 milliwatts average

#### Insertion Loss At Minimum Attenuation In Maximum Decibels:

2.0

#### **Overall Attenuation Range In Decibels:**

+0.0/+10.0

#### **Attenuation Variation Method:**

Continuous

#### Frequency Range:

Between 0.000 megahertz and 400.000 megahertz

#### Adjustment Device Type And Quantity:

1 slotted screw

#### Impedance Rating In Ohms:

50.0 input-output

#### Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

Yes - demil/mli

# NSN 5985-00-509-1182

Variable Attenuator - Page 2 of 2

**Fiig:** A223a0

