NSN 5985-00-513-2856

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-513-2856 **Application Design:** Transmission line **Body Material: Brass Body Style:** Round, terminal/terminals in opposite surface **Terminal Material:** Brass **Terminal Surface Treatment:** Silver plated **Body Surface Treatment:** Silver plated, qq-s-365 **Overall Length:** 2.540 inches **Overall Diameter:** 0.590 inches **Voltage Standing Wave Ratio:** 1.20 **Input Impedance Rating In Ohms:** 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Bnc **Power Rating:** 1.0 watts average **Rf Signal Attenuation In Decibels:** 3.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0/+2.0 gigahertz **Attenuation Accuracy Reference Frequency:** 2.0 gigahertz **Attenuation Accuracy In Decibels:** -0.50/+0.50 **Connection Type Per Function:** Female input and male output **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector Frequency Range:

Between 0.000 hertz and 2.000 gigahertz

NSN 5985-00-513-2856

Fixed Attenuator - Page 2 of 2



Precious Material And Location:
External surfaces silver
Precious Material:
Silver
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A20000