NSN 5985-00-517-7220

Fixed Attenuator - Page 1 of 2

Application Design:



View Online at https://aerobasegroup.com/nsn/5985-00-517-7220

Transmission line
Body Material:
Steel, qq-s-763, class 302, 303, 304, 305, 310, or 316
Body Style:
Round, terminal/terminals in opposite surface
Body Surface Treatment:
Gold plated
Overall Length:
2.750 inches
Overall Diameter:
0.830 inches
Operating Tempurature Range:
-55.0/+85.0 degrees celsius
Voltage Standing Wave Ratio:
1.20
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
N
Power Rating:
2.0 watts average and 300.0 watts peak
Rf Signal Attenuation In Decibels:
20.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+3.0 gigahertz
Attenuation Accuracy In Decibels:
-0.30/+0.30
Connection Type Per Function:
Female output and male input
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 3.000 gigahertz
Shelf Life:
N/a
Unit Of Measure:

NSN 5985-00-517-7220

Fixed Attenuator - Page 2 of 2



Demilitarization:

No

Fiig:

A20000