

View Online at <https://aerobasegroup.com/nsn/5985-00-517-9342>

**Application Design:**

Audio

**Body Style:**

Cylindrical w/side terminals

**Overall Length:**

3.000 inches

**Overall Width:**

2.125 inches

**Body Diameter:**

1.750 inches

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

0.938 inches

**Body Length:**

2.062 inches

**Schematic Diagram Designator:**

"t"

**Distance Between Mounting Facility Centers:**

1.250 inches

**Operating Temperature Range:**

-10.0/+65.0 degrees celsius

**Voltage Standing Wave Ratio:**

1.10

**Power Rating:**

750.0 milliwatts average

**Mounting Facility Screw Thread Series Designator:**

Unc

**Insertion Loss At Minimum Attenuation In Maximum Decibels:**

0.1

**Overall Attenuation Range In Decibels:**

+0.0/+60.0

**Attenuation Variation Method:**

Stepped

**Step Position Quantity:**

20

**Attenuation Per Step In Decibels:**

3.0

**Mounting Facility Type And Quantity:**

4 threaded hole

**Frequency Range:**

Between 20.000 kilohertz and 200.000 kilohertz

**Overall Attenuation Accuracy In Decibels:**

-0.30/+0.30

**Mounting Thread Quantity:**

32 per inch

**Adjustment Device Type And Quantity:**

1 shaft

**Mounting Facility Pattern:**

Two position in-line

**Shaft Type:**

Round

**Mounting Facility Screw Thread Diameter:**

0.138 inches

**Impedance Rating In Ohms:**

600.0 input-output

**Precious Material And Location:**

Contacts silver

**Precious Material:**

Silver

**Test Data Document:**

61967-82340 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A223a0