

View Online at <https://aerobasegroup.com/nsn/5985-00-517-9342>

Application Design:

Audio

Body Style:

Cylindrical w/side terminals

Overall Length:

3.000 inches

Overall Width:

2.125 inches

Body Diameter:

1.750 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.938 inches

Body Length:

2.062 inches

Schematic Diagram Designator:

"t"

Distance Between Mounting Facility Centers:

1.250 inches

Operating Temperature Range:

-10.0/+65.0 degrees celsius

Voltage Standing Wave Ratio:

1.10

Power Rating:

750.0 milliwatts average

Mounting Facility Screw Thread Series Designator:

Unc

Insertion Loss At Minimum Attenuation In Maximum Decibels:

0.1

Overall Attenuation Range In Decibels:

+0.0/+60.0

Attenuation Variation Method:

Stepped

Step Position Quantity:

20

Attenuation Per Step In Decibels:

3.0

Mounting Facility Type And Quantity:

4 threaded hole

Frequency Range:

Between 20.000 kilohertz and 200.000 kilohertz

Overall Attenuation Accuracy In Decibels:

-0.30/+0.30

Mounting Thread Quantity:

32 per inch

Adjustment Device Type And Quantity:

1 shaft

Mounting Facility Pattern:

Two position in-line

Shaft Type:

Round

Mounting Facility Screw Thread Diameter:

0.138 inches

Impedance Rating In Ohms:

600.0 input-output

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Test Data Document:

61967-82340 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0