NSN 5985-00-519-6873

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-519-6873

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b second flange single connection facility

Thread Direction:

Right-hand second flange single connection facility

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

3

Flange Inside Width:

0.705 inches third flange

Flange Inside Height:

0.394 inches third flange

Flange Outside Width:

1.312 inches second flange

Flange Outside Height:

1.312 inches second flange

Flange Inside Diameter:

1.000 inches second flange

Flange Outside Diameter:

3.430 inches third flange

Flange Depth:

0.440 inches third flange

Flange Connecting Hole Diameter:

0.177 inches third flange single connection facility

Voltage Standing Wave Ratio:

1.08

Maximum Operating Pressure:

15.0 pounds per square inch gage

Waveguide Outside Width:

0.702 inches

Thread Size:

0.138 inches second flange single connection facility

Waveguide Inside Width:

0.622 inches

Waveguide Inside Height:

0.311 inches

Waveguide Outside Height:

0.391 inches

Flange Connecting Facility And Quantity:

6 unthreaded hole third flange single connection facility

NSN 5985-00-519-6873

Waveguide Assembly - Page 2 of 2

Flange Style:



Cover type third flange Waveguide Length: 7.020 inches Flexibility: Rigid single tubing segment Material: Copper alloy all flange Surface Treatment: Silver all flange inside surfaces Style Designator: Straight type **Thread Series Designator:** Unc second flange single connection facility **Fsc Application Data:** Radar equipment, except airborne Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** Yes - demil/mli Fiig: A073a0