# NSN 5985-00-519-6877

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-519-6877

#### **Cross Sectional Shape:**

Internal, rectangular external, rectangular

## Bend Angle In Deg:

90.0 single bend h-plane

#### **Tubing Wall Construction Style:**

Seamless single tubing segment

Flange Quantity:

2

#### Flange Inside Width:

0.622 inches second flange

#### Flange Inside Height:

0.311 inches second flange

#### Flange Outside Width:

1.312 inches second flange

#### Flange Outside Height:

1.312 inches second flange

#### Flange Inside Diameter:

1.000 inches second flange

# Flange Depth:

0.375 inches second flange

# Flange Connecting Hole Diameter:

0.147 inches second flange single connection facility

#### **Voltage Standing Wave Ratio:**

1.08

### **Maximum Operating Pressure:**

15.0 pounds per square inch gage

# **Waveguide Outside Width:**

0.702 inches

#### Waveguide Inside Width:

0.622 inches

### **Waveguide Inside Height:**

0.311 inches

#### **Waveguide Outside Height:**

0.391 inches

#### **Waveguide Longer Offset Distance:**

2.610 inches

# Flange Connecting Facility And Quantity:

4 unthreaded hole second flange single connection facility

# Flange Style:

Choke type first flange

#### **Waveguide Offset Distance:**

2.320 inches

# **NSN 5985-00-519-6877** Waveguide Assembly - Page 2 of 2



Flexibility:
Rigid single tubing segment
Material:
Copper alloy all flange
<b>Precious Material And Location:</b>
Flange surface silver
Precious Material:
Silver
Surface Treatment:
Enamel all flange outside surfaces
Style Designator:
Bend type
Fsc Application Data:
Radar equipment, except airborne
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:

A073a0