

View Online at <https://aerobasegroup.com/nsn/5985-00-529-9369>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

Tubing Wall Construction Style:

Convolute single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.005 inches second flange

Flange Inside Height:

0.505 inches second flange

Flange Outside Width:

1.625 inches second flange

Flange Outside Height:

1.625 inches first flange

Flange Inside Diameter:

1.422 inches first flange

Flange Depth:

0.438 inches second flange

Flange Connecting Hole Diameter:

0.169 inches second flange all connection facilities

Voltage Standing Wave Ratio:

1.12

Thready Qty Per Inch (tpi):

32 first flange all connection facilities

Maximum Operating Pressure:

45.0 pounds per square inch gage

Waveguide Outside Width:

1.000 inches

Thread Size:

0.164 inches first flange all connection facilities

Waveguide Inside Width:

0.900 inches

Waveguide Inside Height:

0.400 inches

Waveguide Outside Height:

0.500 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole second flange all connection facilities

Flange Style:

Cover type second flange

Waveguide Length:

1.500 feet

Flexibility:

Flexible single tubing segment

Material:

Rubber synthetic single tubing jacket

Precious Material And Location:

All surfaces silver

Precious Material:

Silver

Surface Treatment:

Silver all tubing segment and flange all surfaces

Style Designator:

Straight type

Thread Series Designator:

Unc first flange all connection facilities

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiiig:

A073a0