NSN 5985-00-531-9625

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-531-9625

Application Design:
Audio
Body Style:
Cylindrical w/side terminals
Overall Length:
2.685 inches
Overall Width:
2.730 inches
Body Diameter:
2.340 inches
Scale Linearity:
Linear
Scale Division Quantity:
10
Shaft Diameter:
0.250 inches
Shaft Length:
0.625 inches
Body Length:
2.060 inches
Schematic Diagram Designator:
Bridged "t"
Distance Between Mounting Facility Centers:
1.500 inches
Mounting Facility Screw Thread Series Designator:
Unef
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.0
Overall Attenuation Range In Decibels:
+1.0/+10.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
10
Attenuation Per Step In Decibels:
1.0
Mounting Facility Type And Quantity:
2 threaded hole
Frequency Range:
Between 0.000 megahertz and 10.000 megahertz
Overall Attenuation Accuracy in Decidels:

-0.25/+0.25

NSN 5985-00-531-9625 Variable Attenuator - Page 2 of 2



Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 shaft
Mounting Facility Pattern:
Two position in-line
Shaft Type:
Round, slotted
Mounting Facility Screw Thread Diameter:
0.250 inches
Impedance Rating In Ohms:
75.0 input-output
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
Yes - demil/mli
Fiig:
A223a0