

View Online at <https://aerobasegroup.com/nsn/5985-00-535-7012>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

Tubing Wall Construction Style:

Seamless all tubing segment

Flange Quantity:

2

Flange Inside Width:

1.003 inches second flange and 1.006 inches second flange

Flange Inside Height:

0.503 inches second flange and 0.506 inches second flange

Flange Outside Width:

1.610 inches second flange and 1.640 inches second flange

Flange Outside Height:

1.610 inches first flange and 1.640 inches first flange

Flange Depth:

0.423 inches second flange and 0.453 inches second flange

Flange Connecting Hole Diameter:

0.169 inches second flange all connection facilities and 0.172 inches second flange all connection facilities

Voltage Standing Wave Ratio:

1.05

Waveguide Outside Width:

Between 0.996 inches and 1.004 inches

Thread Size:

0.138 inches first flange all connection facilities

Waveguide Inside Width:

Between 0.896 inches and 0.904 inches

Waveguide Inside Height:

Between 0.396 inches and 0.404 inches

Waveguide Outside Height:

Between 0.496 inches and 0.504 inches

Waveguide Longer Offset Distance:

12.125 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole second flange all connection facilities

Flange Style:

Cover type second flange

Waveguide Offset Distance:

3.875 inches

Flexibility:

Rigid second tubing segment

Material:

Copper alloy first tubing segment

Surface Treatment:

Enamel all flange outside surfaces

Style Designator:

Corner type

Thread Series Designator:

Unc first flange all connection facilities

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A073a0