

View Online at <https://aerobasegroup.com/nsn/5985-00-538-5352>

**Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:**

2b first flange all connection facilities

**Thread Direction:**

Right-hand first flange all connection facilities

**Tubing Wall Construction Style:**

Seamless single tubing segment

**Flange Quantity:**

2

**Flange Inside Width:**

3.002 inches second flange and 3.005 inches second flange

**Flange Inside Height:**

1.502 inches second flange and 1.505 inches second flange

**Flange Outside Diameter:**

5.298 inches first flange and 5.328 inches first flange

**Flange Depth:**

1.235 inches first flange and 1.265 inches first flange

**Flange Connecting Hole Diameter:**

0.257 inches second flange all connection facilities and 0.260 inches second flange all connection facilities

**Insertion Loss In Decibels:**

0.05

**Thready Qty Per Inch (tpi):**

20 first flange all connection facilities

**Waveguide Outside Width:**

Between 2.994 inches and 3.006 inches

**Thread Size:**

0.250 inches first flange all connection facilities

**Waveguide Inside Width:**

Between 2.334 inches and 2.846 inches

**Waveguide Inside Height:**

Between 1.334 inches and 1.346 inches

**Waveguide Outside Height:**

Between 1.494 inches and 1.506 inches

**Flange Connecting Facility And Quantity:**

8 unthreaded hole second flange all connection facilities

**Flange Style:**

Cover type second flange

**Waveguide Length:**

2.000 feet

**Flexibility:**

Flexible single tubing segment

**Material:**

Copper alloy all tubing segment and flange

**Precious Material And Location:**

Flange surface silver

**Precious Material:**

Silver

**Surface Treatment:**

Silver all flange inside surfaces

**Style Designator:**

Straight type

**Thread Series Designator:**

Unc first flange all connection facilities

**Fsc Application Data:**

Antennas, waveguides, and related equipment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A073a0