

View Online at <https://aerobasegroup.com/nsn/5985-00-539-3071>

Body Style:

Rectangular

Overall Length:

1.320 inches

Overall Height:

0.410 inches

Overall Width:

0.610 inches

Frequency Rating:

0.0 megahertz and 500.0 megahertz single frequency voltage standing wave ratio

Unthreaded Mounting Hole Diameter:

Between 0.115 inches and 0.125 inches

Switch Type:

Nontransfer

Distance Between Mounting Facility Centers:

1.068 inches single mounting facility pattern and 1.088 inches single mounting facility pattern

Operating Temperature Range:

-65.0/+125.0 degrees celsius

Voltage Standing Wave Ratio:

1.20 single

Insertion Loss In Decibels:

0.40 single

Rf Power Handling Capability:

200.0 watts peak single

Minimum Crosstalk Rating In Decibels:

50.0 single

Actuator Operating Method:

Relay

Actuator Current Type And Rating In Amps:

2.0 dc

Actuator Voltage In Volts:

28.0

Switch Operation Sequence:

Makes before breaks

Switch Return Mechanism Type:

Fail-safe

Pole Quantity:

2

Throw Quantity:

2

Coupling Position Quantity:

4

Mounting Facility Type And Quantity:

2 unthreaded hole

Mounting Facility Pattern:

Two position in-line single mounting facility pattern

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A158a0