# NSN 5985-00-541-7714

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-541-7714

## **Cross Sectional Shape:**

Internal, rectangular external, rectangular

#### Bend Angle In Deg:

90.0 single bend e-plane

#### **Tubing Wall Construction Style:**

Corrugated single tubing segment

#### Flange Quantity:

2

#### Flange Inside Width:

0.897 inches all flanges and 0.903 inches all flanges

#### Flange Inside Height:

0.397 inches all flanges and 0.403 inches all flanges

#### Flange Outside Width:

2.070 inches all flanges and 2.110 inches all flanges

#### Flange Outside Height:

1.570 inches all flanges and 1.610 inches all flanges

#### Flange Depth:

0.480 inches all flanges and 0.520 inches all flanges

## Flange Connecting Hole Diameter:

0.167 inches all flanges single connection facility and 0.171 inches all flanges single connection facility

# **Voltage Standing Wave Ratio:**

1.10

#### **Insertion Loss In Decibels:**

0.10

#### **Maximum Operating Pressure:**

10.0 pounds per square inch gage

#### **Waveguide Outside Width:**

Between 0.996 inches and 1.004 inches

#### **Waveguide Inside Width:**

Between 0.896 inches and 0.904 inches

# Waveguide Inside Height:

Between 0.396 inches and 0.404 inches

#### **Waveguide Outside Height:**

Between 0.496 inches and 0.504 inches

# **Waveguide Longer Offset Distance:**

4.430 inches

#### Flange Connecting Facility And Quantity:

8 unthreaded hole all flanges single connection facility

#### Flange Style:

Contact type all flanges

#### **Waveguide Offset Distance:**

1.119 inches

# NSN 5985-00-541-7714

Waveguide Assembly - Page 2 of 2



Flexibility:
--------------

Rigid single tubing segment

Material:

Beryllium single tubing segment

**Surface Treatment:** 

Paint all flange outside surfaces

Style Designator:

Corner type

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0