

View Online at <https://aerobasegroup.com/nsn/5985-00-543-1474>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange single connection facility

Thread Direction:

Right-hand first flange single connection facility

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.253 inches second flange

Flange Inside Height:

0.628 inches second flange

Flange Outside Width:

1.875 inches second flange

Flange Outside Height:

1.875 inches second flange

Flange Inside Diameter:

1.625 inches first flange

Flange Depth:

0.625 inches first flange

Flange Connecting Hole Diameter:

0.169 inches second flange single connection facility

Voltage Standing Wave Ratio:

1.10

Insertion Loss In Decibels:

0.07

Waveguide Outside Width:

1.250 inches

Thread Size:

0.164 inches first flange single connection facility

Waveguide Inside Width:

1.122 inches

Waveguide Inside Height:

0.497 inches

Waveguide Outside Height:

0.625 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole second flange single connection facility

Flange Style:

Cover type second flange

Waveguide Length:

1.000 feet

Flexibility:

Flexible all tubing segment

Material:

Copper alloy all flange

Precious Material And Location:

Flange surface silver

Precious Material:

Silver

Surface Treatment:

Silver all flange inside surfaces

Style Designator:

Straight type

Thread Series Designator:

Unc first flange single connection facility

Fsc Application Data:

Radar equipment, except airborne

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0