## NSN 5985-00-543-1474

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-543-1474

## **Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:** 

2b first flange single connection facility

**Thread Direction:** 

Right-hand first flange single connection facility

**Tubing Wall Construction Style:** 

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.253 inches second flange

Flange Inside Height:

0.628 inches second flange

Flange Outside Width:

1.875 inches second flange

Flange Outside Height:

1.875 inches second flange

Flange Inside Diameter:

1.625 inches first flange

Flange Depth:

0.625 inches first flange

Flange Connecting Hole Diameter:

0.169 inches second flange single connection facility

**Voltage Standing Wave Ratio:** 

1.10

**Insertion Loss In Decibels:** 

0.07

**Waveguide Outside Width:** 

1.250 inches

**Thread Size:** 

0.164 inches first flange single connection facility

Waveguide Inside Width:

1.122 inches

Waveguide Inside Height:

0.497 inches

**Waveguide Outside Height:** 

0.625 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole second flange single connection facility

Flange Style:

Cover type second flange

## **NSN 5985-00-543-1474** Waveguide Assembly - Page 2 of 2



Waveguide Length:
1.000 feet
Flexibility:
Flexible all tubing segment
Material:
Copper alloy all flange
Precious Material And Location:
Flange surface silver
Precious Material:
Silver
Surface Treatment:
Silver all flange inside surfaces
Style Designator:
Straight type
Thread Series Designator:
Unc first flange single connection facility
Fsc Application Data:
Radar equipment, except airborne
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A073a0