## NSN 5985-00-545-4775

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-545-4775

## **Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:** 

2b all flanges single connection facility

**Thread Direction:** 

Right-hand all flanges single connection facility

Bend Angle In Deg:

57.0 single bend h-plane

**Tubing Wall Construction Style:** 

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.897 inches all flanges and 0.903 inches all flanges

Flange Inside Height:

0.397 inches all flanges and 0.403 inches all flanges

Flange Outside Width:

2.070 inches all flanges and 2.110 inches all flanges

Flange Outside Height:

1.570 inches all flanges and 1.610 inches all flanges

Flange Depth:

0.480 inches all flanges and 0.520 inches all flanges

**Voltage Standing Wave Ratio:** 

1.07

**Insertion Loss In Decibels:** 

0.25

**Maximum Operating Pressure:** 

10.0 pounds per square inch gage

**Waveguide Outside Width:** 

Between 0.996 inches and 1.004 inches

**Thread Size:** 

0.164 inches all flanges single connection facility

Waveguide Inside Width:

Between 0.896 inches and 0.904 inches

**Waveguide Inside Height:** 

Between 0.396 inches and 0.404 inches

**Waveguide Outside Height:** 

Between 0.496 inches and 0.504 inches

Flange Connecting Facility And Quantity:

8 threaded hole all flanges single connection facility

Flange Style:

Contact type all flanges

## NSN 5985-00-545-4775

Waveguide Assembly - Page 2 of 2



FI	ex	ib	ili	ty	:

Rigid single tubing segment

Material:

Aluminum alloy single tubing segment

**Surface Treatment:** 

Paint all tubing segment and flange outside surfaces

**Thread Series Designator:** 

Unc all flanges single connection facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0