

View Online at <https://aerobasegroup.com/nsn/5985-00-545-4812>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Bend Angle In Deg:

90.0 second bend h-plane

Tubing Wall Construction Style:

Seamless single tubing segment

Tubing Twist Type:

Straight twist single tubing segment

Tubing Twist Angle In Deg:

45.0 single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.118 inches all flanges and 1.126 inches all flanges

Flange Inside Height:

0.493 inches all flanges and 0.501 inches all flanges

Flange Outside Width:

2.480 inches all flanges and 2.520 inches all flanges

Flange Outside Height:

1.770 inches second flange

Flange Depth:

0.480 inches all flanges and 0.570 inches all flanges

Flange Connecting Hole Diameter:

0.167 inches all flanges single connection facility and 0.171 inches all flanges single connection facility

Voltage Standing Wave Ratio:

1.15

Insertion Loss In Decibels:

0.16

Maximum Operating Pressure:

10.0 pounds per square inch gage

Waveguide Outside Width:

Between 1.246 inches and 1.254 inches

Waveguide Inside Width:

Between 1.118 inches and 1.126 inches

Waveguide Inside Height:

Between 0.493 inches and 0.501 inches

Waveguide Outside Height:

Between 0.621 inches and 0.629 inches

Flange Connecting Facility And Quantity:

8 unthreaded hole all flanges single connection facility

Flange Style:

Contact type all flanges

Waveguide Center To Center Distance:

2.990 feet

Waveguide Height:

6.813 inches

Flexibility:

Rigid single tubing segment

Material:

Aluminum alloy single tubing segment

Surface Treatment:

Oxide film single tubing segment outside surfaces and enamel single tubing segment outside surfaces

Style Designator:

Double bend type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0