

View Online at <https://aerobasegroup.com/nsn/5985-00-545-4854>

**Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Bend Angle In Deg:**

90.0 first bend e-plane

**Tubing Wall Construction Style:**

Seamless single tubing segment

**Flange Quantity:**

2

**Flange Inside Width:**

1.118 inches all flanges and 1.126 inches all flanges

**Flange Inside Height:**

0.493 inches all flanges and 0.501 inches all flanges

**Flange Outside Width:**

2.480 inches all flanges and 2.520 inches all flanges

**Flange Outside Height:**

1.730 inches all flanges and 1.770 inches all flanges

**Flange Depth:**

0.480 inches all flanges and 0.520 inches all flanges

**Flange Connecting Hole Diameter:**

0.167 inches all flanges single connection facility and 0.171 inches all flanges single connection facility

**Voltage Standing Wave Ratio:**

1.10

**Insertion Loss In Decibels:**

0.15

**Maximum Operating Pressure:**

10.0 pounds per square inch gage

**Waveguide Outside Width:**

Between 1.246 inches and 1.254 inches

**Waveguide Inside Width:**

Between 1.118 inches and 1.126 inches

**Waveguide Inside Height:**

Between 0.493 inches and 0.501 inches

**Waveguide Outside Height:**

Between 0.621 inches and 0.629 inches

**Waveguide Longer Offset Distance:**

3.333 feet

**Flange Connecting Facility And Quantity:**

8 unthreaded hole all flanges single connection facility

**Flange Style:**

Contact type all flanges

**Waveguide Offset Distance:**

Between 0.985 inches and 1.015 inches

**Special Features:**

Tubing wall construction can also be laminated

**Flexibility:**

Rigid single tubing segment

**Material:**

Aluminum alloy single tubing segment

**Surface Treatment:**

Oxide film single tubing segment inside surfaces

**Style Designator:**

Bend type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A073a0