NSN 5985-00-548-4130

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-548-4130

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b all flanges single connection facility

Thread Direction:

Right-hand all flanges single connection facility

Bend Angle In Deg:

90.0 all bends e-plane

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.897 inches all flanges and 0.903 inches all flanges

Flange Inside Height:

0.397 inches all flanges and 0.403 inches all flanges

Flange Outside Width:

2.070 inches all flanges and 2.110 inches all flanges

Flange Outside Height:

1.570 inches all flanges and 1.610 inches all flanges

Flange Depth:

0.480 inches all flanges and 0.520 inches all flanges

Voltage Standing Wave Ratio:

1.07

Insertion Loss In Decibels:

0.03

Maximum Operating Pressure:

10.0 pounds per square inch gage

Waveguide Outside Width:

1.000 inches

Thread Size:

0.164 inches all flanges single connection facility

Waveguide Inside Width:

0.900 inches

Waveguide Inside Height:

0.400 inches

Waveguide Outside Height:

0.500 inches

Flange Connecting Facility And Quantity:

8 threaded hole all flanges single connection facility

Flange Style:

Contact type all flanges

NSN 5985-00-548-4130

Waveguide Assembly - Page 2 of 2



Waveguide Leg Length: 1.230 inches **Waveguide Center To Center Distance:** Between 2.198 inches and 2.218 inches **Waveguide Height:** 2.584 inches **Special Features:** Tubing wall construction can also be laminated Flexibility: Rigid single tubing segment Material: Aluminum alloy single tubing segment **Surface Treatment:** Paint single tubing segment outside surfaces **Style Designator:** U-bend type **Thread Series Designator:** Unc all flanges single connection facility Shelf Life: N/a **Unit Of Measure:** Demilitarization:

Yes - demil/mli

Fiig: A073a0