NSN 5985-00-548-4139

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-548-4139

Cross Sectional Shape:

Internal, rectangular external, rectangular

Bend Angle In Deg:

90.0 second bend e-plane

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.897 inches all flanges and 0.903 inches all flanges

Flange Inside Height:

0.397 inches all flanges and 0.403 inches all flanges

Flange Outside Width:

2.070 inches all flanges and 2.110 inches all flanges

Flange Outside Height:

1.570 inches all flanges and 1.610 inches all flanges

Flange Depth:

0.480 inches all flanges and 0.520 inches all flanges

Flange Connecting Hole Diameter:

0.167 inches all flanges single connection facility and 0.171 inches all flanges single connection facility

Voltage Standing Wave Ratio:

1.10

Insertion Loss In Decibels:

0.05

Maximum Operating Pressure:

10.0 pounds per square inch gage

Waveguide Outside Width:

1.000 inches

Waveguide Inside Width:

0.900 inches

Waveguide Inside Height:

0.400 inches

Waveguide Outside Height:

0.500 inches

Flange Connecting Facility And Quantity:

10 unthreaded hole all flanges single connection facility

Flange Style:

Contact type all flanges

Special Features:

Tubing wall construction can also be laminated

Flexibility:

Rigid single tubing segment

NSN 5985-00-548-4139

Waveguide Assembly - Page 2 of 2



B 4	-1-	-:-	ı .
IV	late	rıa	ı-

Aluminum alloy single tubing segment

Surface Treatment:

Paint all tubing segment and flange outside surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0