

View Online at <https://aerobasegroup.com/nsn/5985-00-548-4205>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b all flanges single connection facility

Thread Direction:

Right-hand all flanges single connection facility

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.897 inches all flanges and 0.903 inches all flanges

Flange Inside Height:

0.397 inches all flanges and 0.403 inches all flanges

Flange Outside Width:

2.070 inches all flanges and 2.110 inches all flanges

Flange Outside Height:

1.570 inches all flanges and 1.610 inches all flanges

Flange Depth:

0.480 inches all flanges and 0.520 inches all flanges

Voltage Standing Wave Ratio:

1.10

Insertion Loss In Decibels:

0.05

Maximum Operating Pressure:

10.0 pounds per square inch gage

Waveguide Outside Width:

1.000 inches

Thread Size:

0.164 inches all flanges single connection facility

Waveguide Inside Width:

0.900 inches

Waveguide Inside Height:

0.400 inches

Waveguide Outside Height:

0.500 inches

Flange Connecting Facility And Quantity:

8 threaded hole all flanges single connection facility

Flange Style:

Contact type all flanges

Special Features:

Tubing wall construction can also be laminated

Flexibility:

Rigid single tubing segment

Material:

Aluminum alloy single tubing segment

Surface Treatment:

Paint all tubing segment and flange outside surfaces

Thread Series Designator:

Unc all flanges single connection facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A073a0