

View Online at <https://aerobasegroup.com/nsn/5985-00-548-4230>

**Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:**

2b first flange single connection facility

**Thread Direction:**

Right-hand first flange single connection facility

**Bend Angle In Deg:**

90.0 single bend e-plane

**Tubing Wall Construction Style:**

Seamless single tubing segment

**Flange Quantity:**

2

**Flange Inside Width:**

0.897 inches all flanges and 0.903 inches all flanges

**Flange Inside Height:**

0.397 inches all flanges and 0.403 inches all flanges

**Flange Outside Width:**

2.070 inches all flanges and 2.110 inches all flanges

**Flange Outside Height:**

1.570 inches all flanges and 1.610 inches all flanges

**Flange Depth:**

0.480 inches all flanges and 0.520 inches all flanges

**Flange Connecting Hole Diameter:**

0.167 inches second flange single connection facility and 0.171 inches second flange single connection facility

**Voltage Standing Wave Ratio:**

1.07

**Insertion Loss In Decibels:**

0.06

**Maximum Operating Pressure:**

10.0 pounds per square inch gage

**Waveguide Outside Width:**

Between 0.996 inches and 1.004 inches

**Thread Size:**

0.164 inches first flange single connection facility

**Waveguide Inside Width:**

Between 0.896 inches and 0.904 inches

**Waveguide Inside Height:**

Between 0.396 inches and 0.404 inches

**Waveguide Outside Height:**

Between 0.496 inches and 0.504 inches

**Waveguide Longer Offset Distance:**

4.500 inches

**Flange Connecting Facility And Quantity:**

8 unthreaded hole second flange single connection facility

**Flange Style:**

Contact type all flanges

**Waveguide Offset Distance:**

2.000 inches

**Special Features:**

4.125 in. Dia. Aluminum alloy plate on one end, 2.562 in. From end, plate has six 0.196 in. Dia. Holes equally spaced on 3.625 in. Dia. Bolt circle, tubing wall construction can also be laminated

**Flexibility:**

Rigid single tubing segment

**Material:**

Aluminum alloy single tubing segment

**Surface Treatment:**

Oxide film all tubing segment and flange outside surfaces

**Style Designator:**

Bend type

**Thread Series Designator:**

Unc first flange single connection facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A073a0