

View Online at <https://aerobasegroup.com/nsn/5985-00-548-4232>

**Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:**

2b first flange single connection facility

**Thread Direction:**

Right-hand first flange single connection facility

**Tubing Wall Construction Style:**

Seamless single tubing segment

**Flange Quantity:**

2

**Flange Inside Width:**

1.003 inches second flange and 1.006 inches second flange

**Flange Inside Height:**

0.502 inches second flange and 0.503 inches second flange

**Flange Outside Width:**

1.625 inches first flange

**Flange Outside Height:**

1.625 inches first flange

**Flange Inside Diameter:**

1.216 inches first flange and 1.224 inches first flange

**Flange Depth:**

1.047 inches second flange and 1.078 inches second flange

**Flange Connecting Hole Diameter:**

0.805 inches second flange single connection facility and 0.820 inches second flange single connection facility

**Voltage Standing Wave Ratio:**

1.10

**Insertion Loss In Decibels:**

0.04

**Maximum Operating Pressure:**

10.0 pounds per square inch gage

**Waveguide Outside Width:**

Between 0.996 inches and 1.004 inches

**Thread Size:**

0.164 inches first flange single connection facility

**Waveguide Inside Width:**

Between 0.896 inches and 0.904 inches

**Waveguide Inside Height:**

Between 0.396 inches and 0.404 inches

**Waveguide Outside Height:**

Between 0.496 inches and 0.504 inches

**Flange Connecting Facility And Quantity:**

4 unthreaded hole second flange single connection facility

**Flange Style:**

Contact type second flange

**Waveguide Length:**

6.875 inches

**Flexibility:**

Rigid single tubing segment

**Material:**

Copper alloy single tubing segment

**Surface Treatment:**

Oxide film all tubing segment and flange outside surfaces

**Style Designator:**

Straight type

**Thread Series Designator:**

Unc first flange single connection facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A073a0