

View Online at <https://aerobasegroup.com/nsn/5985-00-548-4278>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange single connection facility

Thread Direction:

Right-hand first flange single connection facility

Bend Angle In Deg:

45.0 all bends e-plane

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.118 inches all flanges and 1.126 inches all flanges

Flange Inside Height:

0.493 inches all flanges and 0.501 inches all flanges

Flange Outside Width:

2.480 inches all flanges and 2.520 inches all flanges

Flange Outside Height:

1.570 inches all flanges and 1.610 inches all flanges

Flange Depth:

0.480 inches all flanges and 0.520 inches all flanges

Flange Connecting Hole Diameter:

0.167 inches second flange single connection facility and 0.171 inches second flange single connection facility

Voltage Standing Wave Ratio:

1.07

Insertion Loss In Decibels:

0.09

Maximum Operating Pressure:

10.0 pounds per square inch gage

Waveguide Outside Width:

Between 1.246 inches and 1.254 inches

Thread Size:

0.164 inches first flange single connection facility

Waveguide Inside Width:

Between 1.118 inches and 1.126 inches

Waveguide Inside Height:

Between 0.493 inches and 0.501 inches

Waveguide Outside Height:

Between 0.621 inches and 0.629 inches

Flange Connecting Facility And Quantity:

8 unthreaded hole second flange single connection facility

Flange Style:

Contact type all flanges

Waveguide Length:

2.099 feet

Waveguide Center To Center Distance:

1.125 inches

Special Features:

Tubing wall construction can also be laminated

Flexibility:

Rigid single tubing segment

Material:

Aluminum alloy single tubing segment

Surface Treatment:

Oxide film all tubing segment and flange outside surfaces

Style Designator:

Offset bend type

Thread Series Designator:

Unc first flange single connection facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0