NSN 5985-00-548-4279

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-548-4279

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange single connection facility

Thread Direction:

Right-hand first flange single connection facility

Bend Angle In Deg:

90.0 first bend e-plane

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.118 inches all flanges and 1.126 inches all flanges

Flange Inside Height:

0.493 inches all flanges and 0.501 inches all flanges

Flange Outside Width:

2.480 inches all flanges and 2.520 inches all flanges

Flange Outside Height:

1.730 inches all flanges and 1.770 inches all flanges

Flange Depth:

0.480 inches all flanges and 0.520 inches all flanges

Flange Connecting Hole Diameter:

0.167 inches second flange single connection facility and 0.171 inches second flange single connection facility

Voltage Standing Wave Ratio:

1.10

Insertion Loss In Decibels:

0.06

Maximum Operating Pressure:

10.0 pounds per square inch gage

Waveguide Outside Width:

Between 1.246 inches and 1.254 inches

Thread Size:

0.164 inches first flange single connection facility

Waveguide Inside Width:

Between 1.118 inches and 1.126 inches

Waveguide Inside Height:

Between 0.493 inches and 0.501 inches

Waveguide Outside Height:

Between 0.621 inches and 0.629 inches

Flange Connecting Facility And Quantity:

8 unthreaded hole second flange single connection facility

NSN 5985-00-548-4279 Waveguide Assembly - Page 2 of 2



1.635 inches Flange Style: Contact type all flanges Waveguide Second Leg Length: 2.500 inches Waveguide Third Leg Length: 9.520 inches Waveguide Fourth Leg Length: 1.187 inches Special Features: Tubing wall construction can also be laminated Flexibility: Rigid single tubing segment Material: Aluminum alloy single tubing segment Surface Treatment: Chromate all tubing segment and flange outside surfaces and paint all tubing segment and flange outside surfaces Style Designator: Three bend type Thread Series Designator: Unc first flange single connection facility Fsc Application Data: Antennas, waveguides, and related equipment Shelf Life:
Contact type all flanges Waveguide Second Leg Length: 2.500 inches Waveguide Third Leg Length: 9.520 inches Waveguide Fourth Leg Length: 1.187 inches Special Features: Tubing wall construction can also be laminated Flexibility: Rigid single tubing segment Material: Aluminum alloy single tubing segment Surface Treatment: Chromate all tubing segment and flange outside surfaces and paint all tubing segment and flange outside surfaces Style Designator: Three bend type Thread Series Designator: Unc first flange single connection facility Fsc Application Data: Antennas, waveguides, and related equipment
Waveguide Second Leg Length: 2.500 inches Waveguide Third Leg Length: 9.520 inches Waveguide Fourth Leg Length: 1.187 inches Special Features: Tubing wall construction can also be laminated Flexibility: Rigid single tubing segment Material: Aluminum alloy single tubing segment Surface Treatment: Chromate all tubing segment and flange outside surfaces and paint all tubing segment and flange outside surfaces Style Designator: Three bend type Thread Series Designator: Unc first flange single connection facility Fsc Application Data: Antennas, waveguides, and related equipment
2.500 inches Waveguide Third Leg Length: 9.520 inches Waveguide Fourth Leg Length: 1.187 inches Special Features: Tubing wall construction can also be laminated Flexibility: Rigid single tubing segment Material: Aluminum alloy single tubing segment Surface Treatment: Chromate all tubing segment and flange outside surfaces and paint all tubing segment and flange outside surfaces Style Designator: Three bend type Thread Series Designator: Unc first flange single connection facility Fsc Application Data: Antennas, waveguides, and related equipment
Waveguide Third Leg Length: 9.520 inches Waveguide Fourth Leg Length: 1.187 inches Special Features: Tubing wall construction can also be laminated Flexibility: Rigid single tubing segment Material: Aluminum alloy single tubing segment Surface Treatment: Chromate all tubing segment and flange outside surfaces and paint all tubing segment and flange outside surfaces Style Designator: Three bend type Thread Series Designator: Unc first flange single connection facility Fsc Application Data: Antennas, waveguides, and related equipment
9.520 inches Waveguide Fourth Leg Length: 1.187 inches Special Features: Tubing wall construction can also be laminated Flexibility: Rigid single tubing segment Material: Aluminum alloy single tubing segment Surface Treatment: Chromate all tubing segment and flange outside surfaces and paint all tubing segment and flange outside surfaces Style Designator: Three bend type Thread Series Designator: Unc first flange single connection facility Fsc Application Data: Antennas, waveguides, and related equipment
Waveguide Fourth Leg Length: 1.187 inches Special Features: Tubing wall construction can also be laminated Flexibility: Rigid single tubing segment Material: Aluminum alloy single tubing segment Surface Treatment: Chromate all tubing segment and flange outside surfaces and paint all tubing segment and flange outside surfaces Style Designator: Three bend type Thread Series Designator: Unc first flange single connection facility Fsc Application Data: Antennas, waveguides, and related equipment
1.187 inches Special Features: Tubing wall construction can also be laminated Flexibility: Rigid single tubing segment Material: Aluminum alloy single tubing segment Surface Treatment: Chromate all tubing segment and flange outside surfaces and paint all tubing segment and flange outside surfaces Style Designator: Three bend type Thread Series Designator: Unc first flange single connection facility Fsc Application Data: Antennas, waveguides, and related equipment
Special Features: Tubing wall construction can also be laminated Flexibility: Rigid single tubing segment Material: Aluminum alloy single tubing segment Surface Treatment: Chromate all tubing segment and flange outside surfaces and paint all tubing segment and flange outside surfaces Style Designator: Three bend type Thread Series Designator: Unc first flange single connection facility Fsc Application Data: Antennas, waveguides, and related equipment
Tubing wall construction can also be laminated Flexibility: Rigid single tubing segment Material: Aluminum alloy single tubing segment Surface Treatment: Chromate all tubing segment and flange outside surfaces and paint all tubing segment and flange outside surfaces Style Designator: Three bend type Thread Series Designator: Unc first flange single connection facility Fsc Application Data: Antennas, waveguides, and related equipment
Flexibility: Rigid single tubing segment Material: Aluminum alloy single tubing segment Surface Treatment: Chromate all tubing segment and flange outside surfaces and paint all tubing segment and flange outside surfaces Style Designator: Three bend type Thread Series Designator: Unc first flange single connection facility Fsc Application Data: Antennas, waveguides, and related equipment
Rigid single tubing segment Material: Aluminum alloy single tubing segment Surface Treatment: Chromate all tubing segment and flange outside surfaces and paint all tubing segment and flange outside surfaces Style Designator: Three bend type Thread Series Designator: Unc first flange single connection facility Fsc Application Data: Antennas, waveguides, and related equipment
Material: Aluminum alloy single tubing segment Surface Treatment: Chromate all tubing segment and flange outside surfaces and paint all tubing segment and flange outside surfaces Style Designator: Three bend type Thread Series Designator: Unc first flange single connection facility Fsc Application Data: Antennas, waveguides, and related equipment
Aluminum alloy single tubing segment Surface Treatment: Chromate all tubing segment and flange outside surfaces and paint all tubing segment and flange outside surfaces Style Designator: Three bend type Thread Series Designator: Unc first flange single connection facility Fsc Application Data: Antennas, waveguides, and related equipment
Surface Treatment: Chromate all tubing segment and flange outside surfaces and paint all tubing segment and flange outside surfaces Style Designator: Three bend type Thread Series Designator: Unc first flange single connection facility Fsc Application Data: Antennas, waveguides, and related equipment
Chromate all tubing segment and flange outside surfaces and paint all tubing segment and flange outside surfaces Style Designator: Three bend type Thread Series Designator: Unc first flange single connection facility Fsc Application Data: Antennas, waveguides, and related equipment
Style Designator: Three bend type Thread Series Designator: Unc first flange single connection facility Fsc Application Data: Antennas, waveguides, and related equipment
Three bend type Thread Series Designator: Unc first flange single connection facility Fsc Application Data: Antennas, waveguides, and related equipment
Thread Series Designator: Unc first flange single connection facility Fsc Application Data: Antennas, waveguides, and related equipment
Unc first flange single connection facility Fsc Application Data: Antennas, waveguides, and related equipment
Fsc Application Data: Antennas, waveguides, and related equipment
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A073a0