NSN 5985-00-548-4293

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-548-4293

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange single connection facility

Thread Direction:

Right-hand first flange single connection facility

Bend Angle In Deg:

90.0 single bend e-plane

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.118 inches second flange and 1.126 inches second flange

Flange Inside Height:

0.493 inches first flange and 0.501 inches first flange

Flange Outside Width:

2.480 inches second flange and 2.520 inches second flange

Flange Outside Height:

1.570 inches second flange and 1.610 inches second flange

Flange Outside Diameter:

2.995 inches first flange and 2.998 inches first flange

Flange Depth:

1.000 inches first flange

Flange Connecting Hole Diameter:

0.167 inches second flange single connection facility and 0.171 inches second flange single connection facility

Voltage Standing Wave Ratio:

1.05

Insertion Loss In Decibels:

0.03

Maximum Operating Pressure:

10.0 pounds per square inch gage

Waveguide Outside Width:

Between 1.246 inches and 1.254 inches

Thread Size:

0.164 inches first flange single connection facility

Waveguide Inside Width:

Between 1.118 inches and 1.126 inches

Waveguide Inside Height:

Between 0.493 inches and 0.501 inches

Waveguide Outside Height:

Between 0.621 inches and 0.629 inches

NSN 5985-00-548-4293 Waveguide Assembly - Page 2 of 2



Waveguide Longer Offset Distance:
4.125 inches
Flange Connecting Facility And Quantity:
8 unthreaded hole second flange single connection facility
Flange Style:
Contact type second flange
Waveguide Offset Distance:
1.625 inches
Special Features:
Tubing wall construction can also be laminated
Flexibility:
Rigid single tubing segment
Material:
Aluminum alloy single tubing segment
Surface Treatment:
Oxide film single tubing segment inside surfaces
Style Designator:
Bend type
Thread Series Designator:
Unc first flange single connection facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:

A073a0