NSN 5985-00-549-4594

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-549-4594 **Application Design:** Transmission line **Body Style:** Irregular **Overall Length:** 6.969 inches **Overall Height:** 1.250 inches **Overall Width:** 2.000 inches **Voltage Standing Wave Ratio:** 1.40 **Power Rating:** 0.5 watts average **Insertion Loss At Minimum Attenuation In Maximum Decibels:** 10.0 **Overall Attenuation Range In Decibels:** +0.0/+20.0 **Attenuation Variation Method:** Stepped **Step Position Quantity:** 6 **Attenuation Per Step In Decibels:** 1.0 and 2.0 and 3.0 and 5.0 and 10.0 and 20.0 **Mounting Facility Type And Quantity:** 2 connector Frequency Range: Between 0.000 hertz and 500.000 megahertz **Overall Attenuation Accuracy In Decibels:** -0.100/+0.100 **Adjustment Device Type And Quantity:** Impedance Rating In Ohms: 50.0 input-output **Terminal Type And Quantity:** 2 connector, receptacle Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5985-00-549-4594

Variable Attenuator - Page 2 of 2



Fiig:

A223a0