

View Online at <https://aerobasegroup.com/nsn/5985-00-549-5761>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Bend Angle In Deg:

90.0 single bend e-plane

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.253 inches all flanges and 1.256 inches all flanges

Flange Inside Height:

0.628 inches all flanges and 0.631 inches all flanges

Flange Outside Width:

1.860 inches all flanges and 1.890 inches all flanges

Flange Outside Height:

1.890 inches second flange

Flange Depth:

0.922 inches all flanges and 0.953 inches all flanges

Flange Connecting Hole Diameter:

0.169 inches all flanges single connection facility and 0.172 inches all flanges single connection facility

Voltage Standing Wave Ratio:

1.05

Insertion Loss In Decibels:

0.05

Maximum Operating Pressure:

10.0 pounds per square inch gage

Waveguide Outside Width:

Between 1.246 inches and 1.254 inches

Waveguide Inside Width:

Between 1.118 inches and 1.126 inches

Waveguide Inside Height:

Between 0.493 inches and 0.501 inches

Waveguide Outside Height:

Between 0.621 inches and 0.629 inches

Waveguide Longer Offset Distance:

1.625 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole all flanges single connection facility

Flange Style:

Cover type all flanges

Waveguide Offset Distance:

1.500 inches

Special Features:

Tubing wall construction can also be laminated

Flexibility:

Rigid single tubing segment

Material:

Aluminum alloy single tubing segment

Surface Treatment:

Oxide film all tubing segment and flange outside surfaces

Style Designator:

Corner type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A073a0