

View Online at <https://aerobasegroup.com/nsn/5985-00-549-5812>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange single connection facility

Thread Direction:

Right-hand first flange single connection facility

Bend Angle In Deg:

90.0 all bends e-plane

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.253 inches second flange and 1.256 inches second flange

Flange Inside Height:

0.628 inches second flange and 0.631 inches second flange

Flange Outside Width:

1.860 inches second flange and 1.890 inches second flange

Flange Outside Height:

1.860 inches second flange and 1.890 inches second flange

Flange Inside Diameter:

1.253 inches first flange and 1.360 inches first flange

Flange Depth:

0.610 inches first flange and 0.640 inches first flange

Flange Connecting Hole Diameter:

0.169 inches second flange single connection facility and 0.172 inches second flange single connection facility

Voltage Standing Wave Ratio:

1.04

Insertion Loss In Decibels:

0.10

Maximum Operating Pressure:

10.0 pounds per square inch gage

Waveguide Outside Width:

Between 1.246 inches and 1.254 inches

Thread Size:

0.164 inches first flange single connection facility

Waveguide Inside Width:

Between 1.118 inches and 1.126 inches

Waveguide Inside Height:

Between 0.493 inches and 0.501 inches

Waveguide Outside Height:

Between 0.621 inches and 0.629 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole second flange single connection facility

Flange Style:

Cover type second flange

Waveguide Length:

4.125 inches

Waveguide Center To Center Distance:

2.625 inches

Flexibility:

Rigid single tubing segment

Material:

Aluminum alloy single tubing segment

Surface Treatment:

Oxide film all flange outside surfaces

Style Designator:

Offset bend type

Thread Series Designator:

Unc first flange single connection facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0